


DOL 20R




Sensor No.	Sensor Name.	Sensor type	Voltage	Size	Non Flushed / Flushed	Output type	On Delay	Off Delay	Sensitivity	Trimmer 1	Trimmer 2	Max run timer	Power rating ohms load	Power rating inductive load $\cos \varphi = 0,8$	Cable length	Factory settings Trimmer 1	Factory settings Trimmer 2
103265	DOL20RR	Relay	90-250VAC	90,5 x 45mm	Flushed	NO and NC	0-600s	1s	0-12mm	Sensitivity	Off Delay	Disabled	1A	0,5A	2m	Middle - 6mm	Counterclockwise - 0s
103266	DOL20R-2T (DOL version)	Relay	90-250VAC	90,5 x 45mm	Flushed	NO and NC	1s	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	1A	0,5A	2m	Middle - 6mm	Middle - 300s


DOL 25




DOL 25 PNP




DOL 25 NPN



DOL 25 SCR - Break




DOL 25 SCR - Make




Sensor No.	Sensor Name.	Sensor type	Voltage	Diameter	Smooth/Thread	Flushed/Non Flushed	Output type	On Delay	Off Delay	Sensitivity	Trimmer 1	Trimmer 2	Max run timer	Connection	Length	Power rating	Cable length	Factory settings Trimmer 1	Factory settings Trimmer 2
102041	DOL25 CA-P-Ø18-NF-CA-SCR-B-2T	SCR	20-250VAC	18mm	Smooth	Non Flushed	Break	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	Middle - 300s
102042	DOL25 CA-P-Ø18-NF-CA-SCR-B-1T	SCR	20-250VAC	18mm	Smooth	Non Flushed	Break	0	0	0-12mm	Sensitivity	-	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	-
102136	DOL25 CA-P-M18-NF-CA-SCR-B-3T	SCR	20-250VAC	18mm	Thread	Non Flushed	Break	30s	0-180s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	Counterclockwise - 0s
102137	DOL25 CA-P-M18-NF-CA-SCR-B-2T	SCR	20-250VAC	18mm	Thread	Non Flushed	Break	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	Middle - 300s
102138	DOL25 CA-P-M18-NF-CA-SCR-B-1T	SCR	20-250VAC	18mm	Thread	Non Flushed	Break	0	0	0-12mm	Sensitivity	-	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	-
102139	DOL25 CA-P-M18-NF-CA-SCR-B-0T	SCR	20-250VAC	18mm	Thread	Non Flushed	Break	0	0	6mm	-	-	Disabled	Cable	101mm	300mA	2m	-	-
102233	DOL25 CA-P-M30-NF-CA-SCR-B-2T	SCR	20-250VAC	30mm	Thread	Non Flushed	Break	0	0-600s	0-25mm	Sensitivity	Off Delay	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	Middle - 300s
102234	DOL25 CA-P-M30-NF-CA-SCR-B-1T	SCR	20-250VAC	30mm	Thread	Non Flushed	Break	0	0	0-25mm	Sensitivity	-	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	-
102913	DOL25-01 CA-P-Ø18-NF-CA-SCR-B-0T	SCR	20-250VAC	18mm	Smooth	Non Flushed	Break	0	1s	6,5mm	-	-	Disabled	Cable	101mm	300mA	2m	-	-
102914	DOL25-60 CA-P-Ø18-NF-CA-SCR-B-0T	SCR	20-250VAC	18mm	Smooth	Non Flushed	Break	0	60s	6,5mm	-	-	Disabled	Cable	101mm	300mA	2m	-	-
102919	DOL25 CA-P-Ø18-NF-CA-SCR-B-2T	SCR	20-250VAC	18mm	Smooth	Non Flushed	Break	0-600s	0	0-12mm	Sensitivity	On Delay	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	Counterclockwise - 0s
102930	DOL25 CA-P-Ø18-NF-CA-SCR-B-2T (AFS03/PUR)	SCR	90-250VAC	18mm	Smooth	Non Flushed	Break	0	5-60s	5,1-12mm	Sensitivity	Off Delay	Disabled	Cable	105mm	300mA	2m	Middle - 8,5mm	Middle - 32s
102934	DOL25 CA-P-Ø18-NF-CA-SCR-B-2T (AFS03/PUR)	SCR	90-250VAC	18mm	Smooth	Non Flushed	Break	0-600s	0	0-12mm	Sensitivity	On Delay	Disabled	Cable	105mm	15mA	2m	Middle - 6mm	Counterclockwise - 0s
102940	DOL25 CA-P-M18-F-CA-SCR-B-2T	SCR	20-250VAC	18mm	Thread	Flushed	Break	0	0-600s	0-8mm	Sensitivity	Off Delay	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	Middle - 300s
102941	DOL25 CA-P-M30-NF-CA-SCR-B-1T	SCR	20-250VAC	30mm	Thread	Non Flushed	Break	0	0	0-25mm	Sensitivity	-	Disabled	Cable	101mm	300mA	2m	Middle - 6mm	-
102942	DOL25 CA-P-M18-NF-CA-SCR-B-0T	SCR	20-250VAC	18mm	Thread	Non Flushed	Break	0	60s	6,5mm	-	-	Disabled	Cable	101mm	300mA	2m	-	-
102943	DOL25 CA-P-M30-NF-CA-SCR-B-0T	SCR	20-250VAC	30mm	Thread	Non Flushed	Break	0	60s	8,3mm	-	-	Disabled	Cable	101mm	300mA	2m	-	-
102944	DOL25 CA-P-Ø18-NF-CA-SCR-B-0T (AFS03/PUR)	SCR	90-250VAC	18mm	Smooth	Non Flushed	Break	0	60s	6,5mm	-	-	Disabled	Cable	105mm	15mA	2m	Clockwise - Disabled	Clockwise - Disabled
102946	DOL25 CA-P-Ø18-NF-CA-SCR-B-2T (AFS03/PUR)	SCR	90-250VAC	18mm	Smooth	Non Flushed	Break	0	1-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	105mm	15mA	2m	Middle - 6mm	Clockwise - 60s
102947	DOL25 CA-P-Ø18-NF-CA-SCR-B-2T (AFS03/PUR)	SCR	90-250VAC	18mm	Smooth	Non Flushed	Break	0	5-60s	5,1-12mm	Sensitivity	Off Delay	Disabled	Cable	105mm	300mA	2m	Middle - 8,5mm	Clockwise - 60s

DOL 26

DOL 26 PNP




DOL 26 NPN



DOL 26 SCR - Break




DOL 26 SCR - Make





Sensor No.	Sensor Name.	Sensor type	Voltage	Diameter	Smooth/Thread	Flushed/Non Flushed	Output type	On Delay	Off Delay	Sensitivity	Trimmer 1	Trimmer 2	Max run timer	Connection	Power rating	Cable length	Factory settings Trimmer 1	Factory settings Trimmer 2	Replacement for
105101	DOL 26 CA-P-M18-NF-CA-SCR-B-2T	SCR	20-280VAC	18mm	Thread	Non Flushed	Break	0	0-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 30s	DOL 25 - 102137, but with diffent delay, 0-60s instead of 0-600s
105102	DOL 26 CA-P-M18-NF-CA-PNP-2-2T	PNP	10-36VDC	18mm	Thread	Non Flushed	NO and NC	0	0-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 30s	DOL 25 - 102097, but with diffent delay, 0-60s instead of 0-600s
105103	DOL 26 CA-P-M18-NF-CA-NPN-2-2T	NPN	10-36VDC	18mm	Thread	Non Flushed	NO and NC	0	0-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 30s	
105104	DOL 26 CA-P-M18-NF-CA-SCR-B-2T	SCR	20-280VAC	18mm	Thread	Non Flushed	Break	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 300s	DOL 25 - 102137
105105	DOL 26 CA-P-M18-NF-CA-SCR-B-2T	SCR	20-280VAC	18mm	Thread	Non Flushed	Break	0-600s	0	0-12mm	Sensitivity	On Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 300s	DOL 25 - 102919, but with tread
105106	DOL 26 CA-P-M18-NF-CA-SCR-M-2T	SCR	20-280VAC	18mm	Thread	Non Flushed	Make	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 300s	DOL 25 - 102929, but with tread
105107	DOL 26 CA-P-Ø18-NF-CA-SCR-B-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0	0-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 30s	AF502 - 102918, but with diffent delay, 0-60s instead of 5-60s
105108	DOL 26 CA-P-Ø18-NF-CA-SCR-B-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 300s	DOL25 - 102941
105109	DOL 26 CA-P-Ø18-NF-CA-SCR-B-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0-600s	0	0-12mm	Sensitivity	On Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 300s	DOL25 - 102919
105110	DOL 26 CA-P-Ø18-NF-CA-SCR-M-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Make	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 300s	DOL25 - 102929 & AF503 - 102932
105111	DOL 26 CA-P-Ø18-NF-CA-SCR-B-0T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0	60s	6mm	-	-	Disabled	Cable	500mA	2m	-	-	DOL25 - 102914, but with different sensitivity, 6mm instead of 6,5mm
105112	DOL 26 CA-P-M18-NF-CA-PNP-2-2T	PNP	10-36VDC	18mm	Thread	Non Flushed	NO and NC	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 300s	DOL25 - 102097
105113	DOL 26 CA-P-M18-NF-CA-NPN-2-2T	NPN	10-36VDC	18mm	Thread	Non Flushed	NO and NC	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	Middle - 300s	
105114	DOL26-CA-P-M18-NF-CA-SCR-B-2T 10M	SCR	20-280VAC	18mm	Thread	Non Flushed	Break	0	5-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	10m	Middle - 6mm	Middle - 30s	
105115	DOL26-CA-P-M18-NF-CA-SCR-M-2T 10M	SCR	20-280VAC	18mm	Thread	Non Flushed	Make	0	5-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	10m	Middle - 6mm	Middle - 30s	
105116	DOL 26 CA-P-Ø18-NF-CA-SCR-B-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0	1-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable	500mA	2m	Middle - 6mm	-	Counterclockwise - 1s
105117	DOL 26 CA-P-M18-NF-CA-SCR-B-0T	SCR	20-280VAC	18mm	Thread	Non Flushed	Break	0	0	6mm	-	-	Disabled	Cable	500mA	2m	-	-	DOL25 - 102139
105201	DOL 26 CA-P-M18-NF-CR-SCR-B-2T	SCR	20-280VAC	18mm	Thread	Non Flushed	Break	0	0-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 30s	
105202	DOL 26 CA-P-M18-NF-CR-PNP-2-2T	PNP	10-36VDC	18mm	Thread	Non Flushed	NO and NC	0	0-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 30s	
105203	DOL 26 CA-P-M18-NF-CR-NPN-2-2T	NPN	10-36VDC	18mm	Thread	Non Flushed	NO and NC	0	0-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 30s	
105204	DOL 26 CA-P-M18-NF-CR-SCR-B-2T	SCR	20-280VAC	18mm	Thread	Non Flushed	Break	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 300s	
105205	DOL 26 CA-P-M18-NF-CR-SCR-B-2T	SCR	20-280VAC	18mm	Thread	Non Flushed	Break	0-600s	0	0-12mm	Sensitivity	On Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 300s	
105206	DOL 26 CA-P-M18-NF-CR-SCR-M-2T	SCR	20-280VAC	18mm	Thread	Non Flushed	Make	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 300s	
105207	DOL 26 CA-P-Ø18-NF-CR-SCR-B-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0	0-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 30s	
105208	DOL 26 CA-P-Ø18-NF-CR-SCR-B-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 300s	
105209	DOL 26 CA-P-Ø18-NF-CR-SCR-B-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0-600s	0	0-12mm	Sensitivity	On Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 300s	
105210	DOL 26 CA-P-Ø18-NF-CR-SCR-M-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Make	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 300s	
105211	DOL 26 CA-P-Ø18-NF-CR-SCR-B-0T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0	60s	6mm	-	-	Disabled	Cable - Return	500mA	2m	-	-	
105212	DOL 26 CA-P-M18-NF-CR-PNP-2-2T	PNP	10-36VDC	18mm	Thread	Non Flushed	NO and NC	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 300s	
105213	DOL 26 CA-P-M18-NF-CR-NPN-2-2T	NPN	10-36VDC	18mm	Thread	Non Flushed	NO and NC	0	0-600s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Middle - 300s	
105216	DOL 26 CA-P-Ø18-NF-CR-SCR-B-2T	SCR	20-280VAC	18mm	Smooth	Non Flushed	Break	0	1-60s	0-12mm	Sensitivity	Off Delay	Disabled	Cable - Return	500mA	2m	Middle - 6mm	Counterclockwise - 1s	

DOL 41 + DOL 43 + DOL 45








Sensor No.	Sensor Name.	Sensor type	Voltage	Size	Smooth/Thread	Output type	On Delay	Off Delay	Sensitivity	Power rating ohms load	Power rating inductive load $\cos \varphi = 0,8$	Cable length	Factory settings - Sensitivity	Factory settings - Delay
100651	DOL 45R	Relay	90-250V AC	30mm	Smooth	NO & NC	0-4hrs.	0-4hrs.	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	30 sec. OFF Delay / 0 sec. ON Delay
100652	DOL 45R	Relay	10-30V AC/DC	30mm	Smooth	NO & NC	0-4hrs.	0-4hrs.	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	30 sec. OFF Delay / 0 sec. ON Delay
100661	DOL 43R	Relay	90-250V AC	30mm	Smooth	NO & NC	-	0-4hrs.	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	30 sec. OFF Delay
100662	DOL 43R	Relay	10-30V AC/DC	30mm	Smooth	NO & NC	-	0-4hrs.	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	30 sec. OFF Delay
100671	DOL 41R	Relay	90-250V AC	30mm	Smooth	NO & NC	-	-	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	-
100672	DOL 41R	Relay	10-30V AC/DC	30mm	Smooth	NO & NC	-	-	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	-
100681	DOL 45R-T	Relay	90-250V AC	30mm	Smooth - With T Fitting	NO & NC	0-4hrs.	0-4hrs.	0-15mm	5A	2A	2m	10mm / Hysteresis 15%	0 sec. OFF Delay / 30 sec. ON Delay
100682	DOL 45R-T	Relay	10-30V AC/DC	30mm	Smooth - With T Fitting	NO & NC	0-4hrs.	0-4hrs.	0-15mm	5A	2A	2m	10mm / Hysteresis 15%	0 sec. OFF Delay / 30 sec. ON Delay
100751	DOL 45R-G	Relay	90-250V AC	30mm	Thread	NO & NC	0-4hrs.	0-4hrs.	0-15mm	5A	2A	2m	10mm / Hysteresis 15%	0 sec. OFF Delay / 30 sec. ON Delay
100752	DOL 45R-G	Relay	10-30V AC/DC	30mm	Thread	NO & NC	0-4hrs.	0-4hrs.	0-15mm	5A	2A	2m	10mm / Hysteresis 15%	0 sec. OFF Delay / 30 sec. ON Delay
100761	DOL 43R-G	Relay	90-250V AC	30mm	Thread	NO & NC	-	0-4hrs.	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	30 sec. OFF Delay
100762	DOL 43R-G	Relay	10-30V AC/DC	30mm	Thread	NO & NC	-	0-4hrs.	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	30 sec. OFF Delay
100771	DOL 41R-G	Relay	90-250V AC	30mm	Thread	NO & NC	-	-	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	-
100772	DOL 41R-G	Relay	10-30V AC/DC	30mm	Thread	NO & NC	-	-	0-15mm	5A	2A	2m	4,5 mm /Hysteresis 20%	-
S100661A	DOL 43R	Relay	90-250V AC	30mm	Smooth	NO & NC	-	0-4hrs.	0-15mm	5A	2A	5m	4,5 mm /Hysteresis 20%	30 sec. OFF Delay
S100662A	DOL 43R	Relay	10-30V AC/DC	30mm	Smooth	NO & NC	-	0-4hrs.	0-15mm	5A	2A	5m	4,5 mm /Hysteresis 20%	30 sec. OFF Delay
S100671A	DOL 41R	Relay	90-250V AC	30mm	Smooth	NO & NC	-	-	0-15mm	5A	2A	5m	4,5 mm /Hysteresis 20%	-
S100672A	DOL 41R	Relay	10-30V AC/DC	30mm	Smooth	NO & NC	-	-	0-15mm	5A	2A	5m	4,5 mm /Hysteresis 20%	-

DOL 44



Sensor No.	Sensor Name.	Sensor type	Voltage	Diameter	Smooth / Thread	Non Flushed / Semi Flushed	Heat	Output type	On Delay	Off Delay	Sensitivity	Trimmer 1	Trimmer 2	Max run timer	Connection	Power rating ohms load	Power rating inductive load cos $\varphi = 0,8$	Cable length	Factory settings Trimmer 1	Factory settings Trimmer 2
100300	DOL 44R-33 capacitive sensor	Relay	90-265V AC	33mm	Smooth	Non Flushed	No	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100301	DOL 44RR-33 capacitive sensor	Relay	90-265V AC	33mm	Smooth	Non Flushed	No	NO and NC	0-600s	0	0-15mm	Sensitivity	On Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100302	DOL 44R-33 capacitive sensor	Relay	90-265V AC	33mm	Smooth	Non Flushed	No	NO and NC	0	0-3600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100304	DOL 44RH-33 capacitive sensor	Relay	90-265V AC	33mm	Smooth	Non Flushed	Yes	NO and NC	0	0-3600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100305	DOL 44RH-33 capacitive sensor	Relay	90-265V AC	33mm	Smooth	Non Flushed	Yes	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100307	DOL 44RRH-33 capacitive sensor	Relay	90-265V AC	33mm	Smooth	Non Flushed	Yes	NO and NC	0-600s	0	0-15mm	Sensitivity	On Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100309	DOL 44R-33 capacitive sensor	Relay	10-30V AC/DC	33mm	Smooth	Non Flushed	No	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100310	DOL 44RR-33 capacitive sensor	Relay	10-30V AC/DC	33mm	Smooth	Non Flushed	No	NO and NC	0-600s	0	0-15mm	Sensitivity	On Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100607	DOL44RG capacitive sensor	Relay	10-30V AC/DC	30mm	Thread	Non Flushed	No	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Middle - 300s
100608	DOL44RG capacitive sensor	Relay	90-265V AC	30mm	Thread	Non Flushed	No	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Middle - 300s
100609	DOL44R capacitive sensor	Relay	10-30V AC/DC	30mm	Smooth	Non Flushed	No	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Middle - 300s
100610	DOL44R capacitive sensor	Relay	90-265V AC	30mm	Smooth	Non Flushed	No	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Middle - 300s
100613	DOL44RR capacitive sensor	Relay	10-30V AC/DC	30mm	Smooth	Non Flushed	No	NO and NC	0-600s	0	0-15mm	Sensitivity	On Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Counterclockwise - 0s
100614	DOL44RR capacitive sensor	Relay	90-265V AC	30mm	Smooth	Non Flushed	No	NO and NC	0-600s	0	0-15mm	Sensitivity	On Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Middle - 300s
100615	DOL44RT capacitive sensor	Relay	90-265V AC	30mm	Smooth	Non Flushed	No	NO and NC	0	0-600s	2-14mm	Sensitivity	On Delay	Disabled	Cable	5A	2A	2m	Middle - 8mm	Middle - 300s
100616	DOL44RT capacitive sensor	Relay	10-30V AC/DC	30mm	Smooth	Non Flushed	No	NO and NC	0	0-600s	2-14mm	Sensitivity	On Delay	Disabled	Cable	5A	2A	2m	Middle - 8mm	Middle - 300s
100617	DOL 44RH capacitive sensor	Relay	90-265V AC	30mm	Smooth	Non Flushed	Yes	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Middle - 300s
100618	DOL 44RHG capacitive sensor	Relay	90-265V AC	30mm	Thread	Non Flushed	Yes	NO and NC	0	0-600s	0-15mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m	Middle - 7,5mm	Middle - 300s
100620	DOL44R capacitive sensor	Relay	90-265V AC	30mm	Smooth	Non Flushed	No	NO and NC	0	0-60s	0-10mm	Sensitivity	Off Delay	Disabled	Cable	5A	2A	2m		



 SCR Make		 Shorted Open
SCR Break		Shorted Open
PNP – NO – Black		VCC Floating
PNP – NC – White		VCC Floating
NPN – NO – Black		Floating GND
NPN – NC - White		Floating GND
Relay - NO		Connected Open
Relay - NC		Connected Open

